



Expandable via SD

- SD card data logging function
- SD card recipe function
- SD card alarm history function

Connectable

- Multiple connection function (1:N, N:1)
- 2 serial interfaces available
- MiniUSB as standard programming interface

Selectable

- Choose between
 12 different models
- Choose between wide variety of features
- Choose between horizontal or vertical mounting

The GT02 offers a host of innovative functions and is also pleasing to the eye. The brilliant 3.8" graphical touch display is illuminated by a maintenance-free, 3-color LED backlight which comes in 2 variations: green/orange/red and white/pink/red. The first SD memory card slot in the three-inch class allows for easy screen data transfer, data logging and storage.

Several other manufacturing requirements were also considered, including a connector location for efficient wiring, an improved environmental IP67 resistance rating, and a newly designed bracket for more secure fastening.

	GT02	2MQ0	GT02	2MQ1	GT02	2MQ2			
Power supply	5V	DC	24V	DC	24V	DC			
Display	3.8" STN monochrome LCD								
Backlight	3-color LED (white/pink/red)								
Resolution	240 x 96 dots								
Displayable characters	216 characters (10-dot font)								
Memory capacity	2MB								
Housing	Hairline silver								
SD/SDHC memory card slot	-		-		*				
RTC	_		_		✓				
USB port	MiniUSB								
Com. Interface	RS232	RS422 (RS485)	RS232	RS422 (RS485)	RS232	RS422 (RS485)			
Dimensions	112 x 74 x 27mm								
Power consumption	1W max.		1.9W max.						
Part number	AIG02MQ03D	AIG02MQ05D	AIG02MQ13D	AIG02MQ15D	AIG02MQ23D	AIG02MQ25D			



	GT02	2GQ0	GT02	2GQ1	GT02	2GQ2			
Power supply	5V	DC	24V	DC	24V DC				
Display	3.8" STN monochrome LCD								
Backlight	3-color LED (green/orange/red)								
Resolution	240 x 96 dots								
Displayable characters	216 characters (10-dot font)								
Memory capacity	2MB								
Housing	Pure black								
SD/SDHC memory card slot	-		-		√				
RTC	-	_		_	✓				
USB port	MiniUSB								
Com. Interface	RS232	RS422 (RS485)	RS232	RS422 (RS485)	RS232	RS422 (RS485)			
Dimensions	112 x 74 x 27mm								
Power consumption	1W	max.	1.9W max.						
Part number	AIG02GQ02D	AIG02GQ04D	AIG02GQ12D	AIG02GQ14D	AIG02GQ22D	AIG02GQ24D			



Accessories:



4GB SDHC card class 2
Part No.: **RP-SDR04GE1A**

MiniUSB cable


Part No.: **CABMINIUSB5**

Front protection sheet Part No.: **AIG02800**

Waterproof packing Part No.: **AIG02810**

Backup battery

Part No.: **AFPX-BATT**



For more information, please see: www.panasonic-electric-works.com